

ML 3320-1

- To enter the MENU set-up ensure the Select light is **not** on and press the SHIFT & MENU button.
- To move through the menu use the GROUP, ITEM and SET buttons.
- When you have finished with the MENU set-up press SHIFT & MENU to save and return to printing mode.

GROUP	ITEM	SET
<b>PRINTER CONTROL</b>	Emulation Mode	<b>IBM PPR, Epson FX</b>
<b>FONT</b>	Print Mode	<b>Utility, NLQ Courier, NLQ Gothic, Draft</b>
	Draft Mode	<b>HSD, SSD</b>
	Pitch	<b>10, 12, 15, 17.1, 20</b>
	Style	<b>Normal, Italics</b>
	Size	<b>Single, Double</b>
	Proportional Spacing	<b>No, Yes</b>
<b>SET-UP</b>	Graphics Printing	<b>Unidirectional, Bi-directional</b>
	7 or 8 Bit Graphics	<b>7, 8</b>
	Receive Buffer Size	1-Line, 16K,28K
	Paper Out Override	<b>No, Yes. (Not for Top Feed)</b>
	Print Registration	<b>0, 0.25,0.2, 0.15, 0.1, 0.05, -0.05, -0.1, -0.15, -0.2, -0.25</b>
	7 or 8 Bits Data Word	<b>8, 7</b>
	Operator Panel Functions	<b>Full Operation, Limited Operation</b>
	Reset Inhibit	<b>No, Yes</b>
	Print Suppress Effective	<b>Yes, No</b>
	Auto LF	<b>No, Yes</b>
	Auto CR (IBM)	<b>No, Yes</b>
	Print DEL Code	<b>No, Yes</b>
	SI Select Pitch (10 CPI) (IBM)	<b>17.1, 15</b>
	SI Select Pitch (12CPI) (IBM)	<b>12, 20</b>
	Time Out Print	<b>Valid, Invalid</b>
	Auto Select	<b>No, Yes</b>
	Centering Position	Default, Mode 1, Mode 2 - 3321 only
	<b>REAR, BOTTOM or TOP FEED</b>	Line Spacing
Form Tear Off		<b>Off, 500ms, 1 Sec, 2 Sec (Rear &amp; Bottom Feed)</b>
Bottom Margin		<b>Valid, Invalid (Top Feed Only)</b>
Skip Over Perforation (Rear & Bottom Feed)		<b>No, Yes</b>
Page Width (136 Column Printer Only)		<b>13.6", 8"</b>
Page Length		<b>12" (Rear &amp; Bottom Feed), 11", 11-2/3" (Top Feed), 14", 17", 3", 4", 5.5", 6", 7", 8", 8.5"</b>
Wait Time		<b>1 sec, 500ms, 2 sec(Top Feed Only)</b>
Page Length Control		<b>By Actual Page Length, MENU setting (Top Feed Only)</b>
<b>SYMBOL SETS</b>	Character Set	Set 2, Set , Standard (ML version), <b>Line Graphics</b> (ML version), Block Graphics (ML version),
	Code Page	<b>USA, Serbo Croatic I, II, French Canadian, ECMA-94, Multilingual, Windows East Europe, Portugal, Windows Greek, Norway, Latin 5(Win Turkey), Baltic 774, Windows Cyrillic, East Europe Latin II-852, Cyrillic I-855, Hungarian CWI, Turkey 857, Ukrainian, Cyrillic II-866, ISO Latin 6, Greek 869, 437,928, Hebrew NC(862), Kamenicky (MJK), Hebrew OC, Windows Hebrew, Greek 437 CYPRUS, Windows Baltic, Turkey, Bulgarian, Polska Mazovia, ISO Latin 2, Serbo Croatic I</b>
	Language Set	<b>ASCII, French, German, British, Danish I, Swedish I, Italian, Spanish I, Japanese, Norwegian, Danish II, Spanish II, Latin American, French Canadian, Dutch, Swedish II, Swedish III, Swedish IV, Turkish, Swiss I, Swiss II, Publisher, TRS 80.</b>
	Slashed Letter O	<b>No, Yes</b>
	Zero Character	<b>Unslashed, Slashed</b>
	<b>PARALLEL INTERFACE</b>	I-Prime
Pin 18		<b>+5v, Open</b>
Auto Feed XT (Epson Only)		<b>Invalid, Valid</b>