

ML 3390-1

- To enter the MENU set-up ensure the Select light is **not** on and press the SHIFT & MENU button.
- To move through the menu use the GROUP, ITEM and SET buttons.
- When you have finished with the MENU set-up press SHIFT & MENU to save and return to printing mode.

GROUP	ITEM	SET
PRINTER CONTROL	Emulation Mode	Epson LQ , IBM PPR, IBM AGM.
FONT	Print Mode	LQ Courier , LQ Swiss, LQ Swiss Bold, LQ Roman, LQ Gothic, LQ Prestige Elite, LQ Orator, Utility
	Pitch	10 , 12, 15, 17.1, 20, Prop
	Style	Normal , Italics
	Size	Single , Double
	Proportional Spacing	No , Yes
SET-UP	Graphics Printing	Unidirectional , Bi-directional
	Max Receive Buffer	8K , 23K, 1-Line.
	Paper Out Override	No , Yes.
	Print Registration	0 , 0.25, 0.2, 0.15, 0.1, 0.05, -0.05, -0.1, -0.15, -0.2, -0.25
	Operator Panel Functions	Full Operation , Limited Operation
	Reset Inhibit	No , Yes
	Print Suppress Effective	Yes , No
	Auto LF	No , Yes
	Auto CR (IBM)	No , Yes
	Graphics Speed	Low , High
	SI Select Pitch (10 CPI) (IBM)	17.1 , 15
	SI Select Pitch (12CPI) (IBM)	12 , 20
	Time Out Print	Valid , Invalid
	Auto Select	No , Yes
	Centering Position	Default, Mode 1, Mode 2 - 3391 only
REAR, BOTTOM or TOP FEED	Line Spacing	6 LPI , 8 LPI
	Form Tear Off	Off , 500ms, 1 Sec, 2 Sec (Rear & Bottom Feed)
	Skip Over Perforation (Rear & Bottom Feed)	No , Yes
	Page Width (136 Column Printer Only)	13.6" , 8"
	Page Length	12" (Rear & Bottom Feed), 11", 11-2/3" (Top Feed), 14", 17", 3", 4", 5.5", 6", 7", 8", 8.5"
	Wait Time	1 sec , 500ms, 2 sec (Top Feed Only)
	Page Length Control	By MENU setting , Actual Page Length
SYMBOL SETS	Character Set	Set 2 , Set 1
	Code Page	USA , Serbo Croatic I, II, French Canadian, ECMA-94, Multilingual, Windows East Europe, Portugal, Windows Greek, Norway, Latin 5 (Win Turkey), Baltic 774, Windows Cyrillic, East Europe Latin II-852, Cyrillic I-855, Hungarian CWI, Turkey 857, Ukrainian, Cyrillic II-866, ISO Latin 6, Greek 869, 437, 928 Hebrew NC(862), Kamenicky (MJK), Hebrew OC, Windows Hebrew, Greek 437 CYPRUS, Windows Baltic, Turkey, Bulgarian, Polska Mazovia, ISO Latin 2, Serbo Croatic I
	Language Set	ASCII , French, German, British, Danish I, Swedish I, Italian, Spanish I, Japanese, Norwegian, Danish II, Spanish II, Latin American, French Canadian, Dutch, Swedish II, Swedish III, Swedish IV, Turkish, Swiss I, Swiss II, Publisher
	Slashed Letter O	No , Yes
	Zero Character	Unslashed , Slashed
PARALLEL INTERFACE	I-Prime	Buffer Print , Invalid, Buffer Clear
	Pin 18	+5v , Open
	Auto Feed XT (Epson)	Invalid , Valid