

# ML 3410

- To enter the MENU set-up turn the printer on, whilst holding the QUIET button down.
- To move through the menu use the GROUP, ITEM and SET buttons.
- When you have finished with the MENU set-up press EXIT to save and return to printing mode.

GROUP	ITEM	SET
<b>PRINTER CONTROL</b>	Emulation Mode	Epson LQ, <b>IBM PPR</b> , IBM X24 AGM
<b>FONT</b>	Print Mode	LQ, NLQ, <b>Utility</b> , HSD – Courier, Swiss, Swiss Bold, Roman, Letter Gothic, Prestige Elite, Cartridge DLL
	Pitch	<b>10</b> , 12, 15, 17.1, 20, CPI, Proportional
	Style	<b>Normal</b> , Italics
	Size	<b>Single</b> , Double
<b>SET-UP</b>	Graphics Printing	Uni-directional, <b>Bi-directional</b>
	Max Receive Buffer	<b>8K</b> , 1 Line, 23K, 40K (Option)
	Paper Out Override	<b>No</b> , Yes.
	Print Registration	<b>0</b> , 0.25, 0.2, 0.15, 0.1, 0.05, -0.05, -0.1, -0.15, -0.2, -0.25
	Operator Panel Functions	<b>Full Operation</b> , Limited Operation
	Reset Inhibit	<b>No</b> , Yes
	Print Suppress Effective	<b>No</b> , Yes
	Auto LF	<b>No</b> , Yes
	Auto CR (IBM)	<b>No</b> , Yes
	CSF Bin Select	<b>Bin 1</b> , Bin 2
	SI Select Pitch (10 CPI) (IBM)	<b>17.1</b> , 15
	SI Select Pitch (12CPI) (IBM)	<b>12</b> , 20
	Time Out Print	<b>Valid</b> , Invalid
	Auto Select	<b>No</b> , Yes
Sensor Disable	<b>No</b> , Yes	
<b>REAR, BOTTOM &amp; CUT SHEET FEEDER</b>	Line Spacing	<b>6 LPI</b> , 8 LPI
	Form Tear Off (Rear & Bottom Feed)	<b>Off</b> , 300ms, 2 Sec, 4 Sec, Off-line
	Skip Over Perforation	<b>No</b> , Yes
	Page Width	<b>13.6"</b> , 8 "
	Page Length	<b>12" (Rear &amp; Bottom)</b> , 11", <b>11-2/3" (CSF)</b> , 14", 16.57", 3", 3.5", 4", 5.5", 6", 7", 8", 8.5"
<b>SYMBOL SETS</b>	Character Set	<b>Set II</b> , Set I
	Code Page	<b>USA</b> , Multilingual, Norway, Portugal, Canada-French, Turkey, Greek_928,_851,_437, Cyrillic, Polska Mazovia, Polska PC Latin2, Servbo Croatic I, II, ECMA-94
	Language Set	<b>American</b> , French, German, British, Danish I, Swedish I, Italian, Spanish I, Japanese, Norwegian, Danish II, Spanish II, Latin American, French Canadian, Dutch, Swedish II, III, IV, Turkish, Swiss I, II, Publisher
	Slashed Letter O	<b>No</b> , Yes
	Zero Character	<b>Unslashed</b> , Slashed
	<b>PARALLEL INTERFACE</b>	I-Prime
Pin 18		<b>+5V</b> , Open
Auto Feed XT (Epson)		<b>Invalid</b> , Valid
<b>SERIAL INTERFACE OPTIONS</b>	Parity	<b>None</b> , Odd, Even
	Serial Data No. of Bits	<b>8</b> , 7
	Protocol	<b>Ready/Busy</b> , X-ON/OFF
	Diagnostic Test	<b>No</b> , Yes
	Busy Line	<b>SSD-</b> , SSD+, DTR, RTS
	Baud Rate	<b>9600</b> , 4800, 2400, 1200, 600, 300, 19200, BPS
	DSR Signal	<b>Valid</b> , Invalid
	DTR Signal	<b>Ready On Power Up</b> , Ready On Select
Busy Time	<b>200ms</b> , 1 Second	