

## ML 380 IBM/ Epson

- To enter the MENU set-up turn on the printer whilst holding the FONT button down.
- To move through the menu use the GROUP, ITEM and SET buttons.
- When you have finished with the MENU set-up press EXIT to save and return to printing mode.

GROUP	ITEM	SET
<b>FONT</b>	Print Mode	<b>LQ Swiss</b> , LQ Courier, LQ Helvetica, LQ Orator, NLQ Utility
	Pitch	<b>10</b> , 12, 15, 17.1, 20 CPI, Proportional
	Style	<b>Normal</b> , Italics
	Size	<b>Single</b> , Double
<b>GENERAL CONTROL</b>	Emulation Mode	<b>Epson LQ</b> , IBM X24 AGM
	Graphics Printing	<b>Unidirectional</b> , Bi-directional
	CSF	<b>Not Installed</b> , Installed
	Max Receive Buffer	<b>8K</b> , 23K, 40K (Option), 1-Line.
	Paper Out Override	<b>No</b> , Yes.
	Print Registration	<b>0</b> , -1, -2, -3, -4, -5, +5, +4, +3, +2, +1
	Operator Panel Functions	<b>Full Operation</b> , Limited Operation
	Reset Inhibit	<b>No</b> , Yes
	Print Suppress Effective	<b>Yes</b> , No
CPU Compensation	<b>Standard</b> , Special	
<b>VERTICAL CONTROL</b>	Line Spacing	<b>6 LPI</b> , 8 LPI
	Form Tear Off	<b>Off</b> , 300ms, 2 Sec, 4 Sec, Off-line
	Skip Over Perforation	<b>No</b> , Yes
	Auto LF	<b>No</b> , Yes
	Auto CR (IBM)	<b>No</b> , Yes
	Menu Line	<b>6</b> , 1
	Page Length	<b>11"</b> , 11-2/3", 12", 14", 16.57", 3", 3.5", 4", 5.5", 6", 7", 8", 8.5"
Sheet Page Length	<b>11-2/3"</b> , 14", 16.57", 3", 3.5", 4", 5.5", 6", 7", 8", 8.5", 11", 12"	
<b>SYMBOL SETS</b>	Character Set	<b>IBM Set II</b> , Epson, IBM Set I
	Code Page	<b>USA</b> , Multilingual, Norway, Portugal, , Turkey
	Language Set	<b>ASCII</b> , French, German, British, Danish I, Swedish I, Italian, Spanish I, Japanese, Norwegian, Danish II, Spanish II, Latin American, French Canadian, Dutch, Swedish II, III, IV, Turkish, Swiss I, II, Publisher
	Zero Character	<b>Unslashed</b> , Slashed
	Slashed Letter O	<b>No</b> , Yes
<b>PARALEL INTERFACE</b>	I-Prime Signal	<b>Valid</b> , Invalid
	Auto Feed XT (Epson)	<b>Invalid</b> , Valid
	Pin 18 Output	<b>5v</b> , 0
<b>SERIAL INTERFACE OPTIONS</b>	Parity	<b>None</b> , Odd, Even
	Serial Data No. of Bits	<b>8</b> , 7
	Protocol	<b>Ready/Busy</b> , X-ON/OFF
	Diagnostic Test	<b>No</b> , Yes
	Busy Line	<b>SSD-</b> , SSD+, DTR, RTS
	Baud Rate	<b>9600</b> , 4800, 2400, 1200, 600, 300, 19200, BPS
	DSR Signal	<b>Valid</b> , Invalid
	DTR Signal	<b>Ready On Power Up</b> , Ready On Select
Busy Time	<b>200ms</b> , 1 Second	